Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Logik

Supplier's address: Customer Services, 3RD FLOOR OFFICE SUITE, OMNI PARK SHOPPING CENTRE,

SANTRY DUBLIN 9, SANTRY, DUBLIN

Model identifier: LKL9621

Type	of light	t source:
------	----------	-----------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	other elec-		
(or other electric interface)	tric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
0,	mption in on- 00 h), rounded st integer	5	Energy efficiency class	G	
dicating if it refe a sphere (360º)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,10	
(P _{net}) for CLS, (tandby power expressed in W the second dec-	0,00	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	85	
Outer dimen-	Height	20	Spectral power dis-	See image	
sions without	Width	955	tribution in the	in last page	
separate con- trol gear, light-	Depth	11	range 250 nm to 800 nm, at full-load		

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-	
			Chromaticity coordi-	0,437	
			nates (x and y)	0,402	
Parameters for LED and OLED light sources:					
R9 colour renderii	ng index value	17	Survival factor	0,90	
the lumen maintenance factor		0,96			

(a)'-': not applicable; (b)'-': not applicable;

