Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2014

Supplier's name or trade mark: HISENSE

Supplier's address: Partizanska 12, 3320 Velenje, SI

Model identifier: HWD3S8514

General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	5,0	Dimensions in cm	Height	85
	Rated			Width	60
	washing capacity	8,0		Depth	51
Energy Efficiency Index	EEIw	36,3	Energy efficiency class	EEIw	А
	EEI _{wd}	66,9		EEI _{wd}	D
Washing efficiency index	I _w	1,031	Rinsing effectiveness (g/kg dry textile)	I _R	5,00
	Jw	1,055		J _R	4,2
Energy consumption in kWh per kg per cycle, for the washing cycle of the household washer- dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used		0,33	for the wash and dry cycle of the ho washerdryer at a combination of fu	ergy consumption in kWh per kg per cycle, the wash and dry cycle of the household sherdryer at a combination of full and half ds. Actual energy consumption will depend how the appliance is used	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water		36	Water consumption in litre per cycl wash and dry cycle of the househol dryer at a combination of full and h Actual water consumption will depe the appliance is used and on the ha the water	ld washer- half loads. 80 end on how	
Maximum temperature inside the treated textile (°C)	Rated washing capacity	28	Weighted remaining moisture	53,0	
	Half	27	content (%)		
	Quarter	25			
Spin speed (rpm)	Rated washing capacity	1400		В	
	Half	1400	Spin-drying efficiency class		
	Quarter	1400			
Eco 40-60 programme duration (h:min)	Rated washing capacity	3:38	wash and dry cycle duration (h:min)	Rated capacity	7:59
	Half	2:48		Half	5:29
	Quarter	2:03		11an 5.25	
Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	72		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	^	
Туре	Free-standing				
Off-mode (W)	0,49		Standby mode (W)	0,49	
Delay start (W)	4,00		Networked standby (W)	2,00	
Minimum duration of the guarante	ee offered by	the manuf	acturer: 24 months		
This product has been designed to release silver ions during the washing cycle				No	
Additional information:					
http://global.hisense.com/					